

SILOCORD®/SP



Dry cargo suction and discharge hose

Marking: Silocord® / SP Zement / Dry - Cargo PN 6 bar - M

Norm	EN ISO 1307:2008, ISO 4649 (previous DIN 53516)	Abrasion value tube	90-110 mm ³
Working pressure	6 bar	Construction tube	Smooth
Vacuum	0,80 bar	Color tube	Black
Min. temperature	-30 °C	Compound cover	SBR
Max. temperature	+80 °C	Cover	Fabric finish
Electr. resistance tube	Electrical conductive <10 ⁶ Ω	Color cover	Black
Electr. resistance cover	Electrical conductive <10 ⁶ Ω	Reinforcements	Static wire, Steel spiral, Textile plies
Compound tube	NR/SBR		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3535076096	76,0	10,0	96,0	310	3,880	40
3535102122	102,0	10,0	122,0	410	5,260	20

Application: Very wear resistant and flexible silo hose with steel spiral that can be used for filling and unloading silos and silo trucks, suitable for highly abrasive materials such as cement, sand, lime powder, animal feed, granulates, wood pellets, etc. Hose is very easy to handle due to its flexible construction and it is one of the safest hoses for this application as the static electricity is discharged through a static wire and the rubber itself also has conductive properties.

Remark:

- Cutted length possible

We recommend assembly with

5123
Storz couplings



5611
Swiveling flange



5560
Safety clamps

