

Ball Valve type 9000



With full flow
and BSP female thread at both sides

Norm thread	DIN EN ISO 228-1
Thread description	BSPP thread / G-thread
Design	Full flow
Min. temperature	-20 °C
Max. temperature	+150 °C
Material seal/gasket	PTFE
Material type body	Chrome plated brass
Ball material	Hard chrome plated hot pressed brass
Colour handle	Red

Art.-no.	Female thread	Bore mm	Built-in length (mm)	WP at 20°C (bar)	Material handle	Weight (kg/pce)
5240006900	1/4"	10	44,4	50,0	Steel	0,118
5240010900	3/8"	10	44,4	50,0	Steel	0,126
5240013900	1/2"	15	50,5	50,0	Steel	0,179
5240019900	3/4"	20	57,5	40,0	Steel	0,297
5240025900	1"	25	70,0	40,0	Steel	0,425
5240032900	1.1/4"	32	80,5	30,0	Steel	0,678
5240038900	1.1/2"	40	94,5	30,0	Steel	1,036
5240050900	2"	50	112,5	25,0	Steel	1,616
5240063900	2.1/2"	65	134,5	18,0	Aluminum	3,430
5240075900	3"	80	157,0	16,0	Aluminum	5,271
5240100900	4"	100	190,0	14,0	Aluminum	8,818

Remark:

- Not suitable for steam applications!

