


RADIACORD®

Cooling water hose



Marking:  Radiacord® PN .. bar max. 100°C

Norm	EN ISO 1307:2008	Color tube	Black
Min. temperature	-30 °C	Compound cover	EPDM
Max. temperature	+100 °C	Color cover	Black
Compound tube	EPDM	Reinforcements	Textile plies
Construction tube	Extruded		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	WP (bar)	Cover	Weight (kg/mtr)	Length (mtr)
3100010000	10,0	3,5	17,0	6	Smooth	0,210	40
3100013000	13,0	3,5	20,0	6	Smooth	0,250	40
3100015000	15,0	3,5	22,0	6	Smooth	0,280	40
3100018000	18,0	3,5	25,0	6	Smooth	0,330	40
3100020000	20,0	3,5	27,0	6	Smooth	0,360	40
3100022000	22,0	3,5	29,0	6	Smooth	0,400	40
3100025000	25,0	3,5	32,0	6	Smooth	0,440	40
3100028000	28,0	3,5	35,0	4	Fabric finish	0,480	40
3100030000	30,0	4,0	38,0	4	Fabric finish	0,520	40
3100032000	32,0	3,5	39,0	4	Fabric finish	0,550	40
3100035000	35,0	3,5	42,0	4	Fabric finish	0,600	40
3100038000	38,0	3,5	45,0	4	Fabric finish	0,640	40
3100040000	40,0	3,5	47,0	4	Fabric finish	0,670	40
3100042000	42,0	3,5	49,0	4	Fabric finish	0,700	40
3100045000	45,0	4,0	53,0	4	Fabric finish	0,850	40
3100048000	48,0	4,0	56,0	4	Fabric finish	0,910	40
3100050000	50,0	4,5	59,0	4	Fabric finish	0,970	40
3100060000	60,0	5,0	70,0	4	Fabric finish	1,320	40
3100063000	63,0	5,0	73,0	4	Fabric finish	1,410	40
3100075000	76,0	4,0	84,0	4	Fabric finish	1,340	40
3100090000	90,0	4,0	98,0	4	Fabric finish	1,500	20
3100100000	102,0	4,0	110,0	4	Fabric finish	1,700	40
3100110000	110,0	6,0	122,0	4	Fabric finish	2,700	20

Application: Suitable as a radiator hose and resistant to the usual antifreeze agents. The hose can also be used for hot water and cooling water applications.

Remark:

- Cutted length possible

We recommend assembly with

5327
Hose coupling



5340
Hose tail



6060
ABA clamps

