

ARIAFORM®/15

Air pressure/water hose



Marking: Ariaform® PN 15 bar PB 45 bar

Norm	EN ISO 1307:2008	Color tube	Black
Working pressure at 20°C	15,0 bar	Compound cover	Thermoplastic elastomer
Bursting pressure	45 bar	Cover	Smooth
Min. temperature	-30 °C	Color cover	Black
Max. temperature	+60 °C	Resistance cover	Ageing resistant, Ozone resistant, UV resistant, Weather resistant
Compound tube	Thermoplastic elastomer	Reinforcements	Polyester plies
Construction tube	Extruded		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3200016026	16,0	5,0	26,0	120	0,450	50
3200019027	19,0	4,5	28,0	150	0,450	25/50
3200025036	25,0	5,5	36,0	200	0,795	40

Application: High quality, thick walled, flexible hose for medium duty applications in industry, maintenance workshops and at construction sites. Suitable for the transport of water and air. Hose is resistant to oil mist.

Remark:

- Cutted length not possible

We recommend assembly with

5219
Claw coupling



6305
Hose Clamps

