

Your partner for Rubber hoses, PVC hoses, couplings and all kind of other appendages.



AIRBRAKE



Bremsschlauch/Airbrake DIN 74310 ID.. week/year Marking: [

13,0

6,0

| Norm | | DIN 74310:1993, EN ISO 1307:2008 | | Construction tube | Smooth, Extruded | |
|--------------------------|-------------|----------------------------------|--------------|---------------------|------------------|--------------|
| Working pressure at 20°C | | 10,0 bar | | Color tube | Black | |
| Bursting pressure | | 25 bar | | Compound cover | EPDM | |
| Min. temperature | | -40 °C | | Cover | Smooth | |
| Max. temperature | | +70 °C | | Color cover | Black | |
| Compound tube | | EPDM | | Reinforcements | Textile plies | |
| Artno. | Ø Inner (mn | n) Wall (mm) | Ø Outer (mm) | Bending radius (mm) | Weight (kg/mtr) | Length (mtr) |
| 3215011018 | 11,0 | 3,5 | 18,0 | 70 | 0,230 | 40 |

Rubber airbrake hose

80

0,500

40

Application: Standardized brake hose for air braking systems of vehicles and other compressed air systems in motor vehicles and trailers. Remark:

25,0

• Cutted length not possible

3215013025

