

SALDAFORM®/RED



Acetylene hose
for welding purposes.

Marking: ISO 3821 - 2MPa (20 bar) - dimension - Saldaform® - year

Norm	EN ISO 1307:2008, ISO 3821:2019	Construction tube	Smooth
Working pressure	20 bar	Color tube	Black
Bursting pressure	60 bar	Compound cover	EPDM
Min. temperature	-30 °C	Cover	Ribbed
Max. temperature	+70 °C	Color cover	Red
Compound tube	EPDM	Reinforcements	Textile plies

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3255006000	6,3	3,5	13,3	40	0,160	50
3255008000	8,0	3,5	15,0	40	0,200	50
3255009000	9,0	3,5	16,0	45	0,220	50
3255013000	0,410					
3255015000	0,470					

Application: Very flexible ribbed hose suitable for transport of acetylene. For welding and cutting, for plasma arc welding (PAW) and other similar processes. Also suitable for hydrogen, syngas (mixture of carbon monoxide and hydrogen gas), carbon dioxide, argon, nitrogen for welding and cutting. Not suitable for LPG, MPS and CNG.

Remark:

- Cutted length not possible

