

SALDAFORM®/RED



Acetylene hose
for welding purposes.

Marking: ISO 3821 - 2MPa (20 bar) - dimension - Saldaform® - year

Norm	EN ISO 1307:2008, ISO 3821:2019	Construction tube	Smooth
Working pressure	20 bar	Color tube	Black
Bursting pressure	60 bar	Compound cover	EPDM
Min. temperature	-30 °C	Cover	Smooth
Max. temperature	+70 °C	Color cover	Red
Compound tube	EPDM	Reinforcements	Textile plies

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3256006000	6,3	3,5	13,3	40	0,160	40
3256009000	9,0	3,5	16,0	45	0,220	40
3256013000	12,5	5,0	22,5	65	0,410	50
3256015000	16,0	5,0	26,0	80	0,470	50

Application: Very flexible smooth hose suitable for transport of acetylene. For welding and cutting, for plasma arc welding (PAW) using shielding gas and other similar processes. Also suitable for hydrogen, coal gas (mixture of carbon monoxide and hydrogen gas), carbon dioxide, argon, nitrogen for welding and cutting. Not suitable for LPG, MPS and CNG.

Remark:

- Cutted length not possible

