

## VAPORCORD®

### Low pressure steam hose



Marking: Vaporcord® Steamhose / Dampfschlauch PN 7 bar - max. 164°C - Hot Water/Heisswasser PN 20 bar max. +95°C

Norm	EN ISO 1307:2008	Electr. resistance cover	Electrical conductive <math><10^6 \Omega</math>
Max. working pressure hot water	20 bar	Compound tube	EPDM
Max. operating pressure steam	7 bar	Construction tube	Smooth
Bursting pressure	70 bar	Color tube	Black
Min. temperature	-35 °C	Compound cover	EPDM
Max. temperature hot water	+95 °C	Cover	Fabric finish, Pin-pricked
Max. temperature steam	+164 °C	Color cover	Black
Electr. resistance tube	Electrical conductive <math><10^6 \Omega</math>	Reinforcements	Textile plies

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3400010000	10,0	5,5	21,0	70	0,360	40
3400013000	13,0	5,5	24,0	80	0,430	40
3400019000	19,0	7,0	33,0	115	0,730	40
3400025000	25,0	7,0	39,0	150	0,900	40
3400032000	32,0	7,5	47,0	195	1,180	40
3400038000	38,0	9,0	56,0	250	1,700	40
3400050000	51,0	9,0	69,0	300	2,100	40
3400063000	63,5	10,0	83,5	450	2,800	40
3400075000	76,0	11,0	98,0	550	3,700	40

**Application:** Flexibel low pressure steam hose for hot water and saturated steam applications. After use, drain water or steam and let the hose dry in a proper way. This significantly reduces the risk of popcorning of the inner wall.

**Remark:**

- Cutted length possible
- Drain the hose after usage

**We recommend assembly with**

5410  
Boss steam couplings



5420  
Boss steam couplings



5430  
Steam couplings

