

HEDUFLEX®/GRECATO



Rubber suction and discharge hose with corrugated cover for drainage water, dung and with limited lye and acid resistance

Marking: Heduflex®/Grecato S/D PN 6 bar

Norm	EN ISO 1307:2008	Construction tube	Smooth
Working pressure	6 bar	Color tube	Black
Bursting pressure	18 bar	Compound cover	SBR
Vacuum	0,90 bar	Cover	Fabric finish, Square corrugated
Min. temperature	-30 °C	Color cover	Black
Max. temperature	+85 °C	Reinforcements	Steel spiral, Textile plies
Compound tube	SBR		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Bending radius (mm)	Weight (kg/mtr)	Length (mtr)
3641075000	76,0	7,0	90,0	228	2,420	40
3641100000	102,0	7,5	117,0	306	3,870	40
3641125000	127,0	8,0	143,0	445	4,980	20
3641150000	152,0	8,0	168,0	608	6,020	20
3641200000	203,0	10,5	224,0	812	10,430	4/6

Application: Very high quality, extra flexible rubber hose. Suitable for (industrial) water and dung. Limited lye and acid resistant. Widely used for industrial, agricultural, machine building, construction, infrastructure and horticultural applications. The hose is very flexible due to the special "Greek" profile and is therefore often used in places where a very small bending radius is required.

Remark:

- Cutted length possible (ID 203 excluded)
- ID 203 with spiral free cuffs

We recommend assembly with

5721
Perrot couplings



5710
Bauer couplings



6202
Mikalor Supra - clamps

