


PYROFLAT®



Layflat firefighting hose
with high tensile strength and flat collapsible.

Marking:  Pyroflat®

Norm	EN ISO 1307:2008	Compound cover	Polyurethane coating
Min. temperature	-40 °C	Color cover	Red
Max. temperature	+80 °C	Resistance cover	Abrasion resistant, UV resistant
Compound tube	EPDM	Reinforcements	2 plies warp polyester threads
Color tube	Black		

Art.-no.	Ø Inner (mm)	Wall (mm)	Ø Outer (mm)	Measured flat (mm)	WP at 20°C (bar)	BP (bar)	Weight (kg/mtr)	Length (mtr)
4022038000	38,0	1,6	41,2	60	20,0	50	0,185	20/30/50
4022050000	52,0	1,8	55,6	82	20,0	50	0,260	20/30/50/100
4022063000	65,0	1,8	68,6	100	20,0	50	0,310	20/50/100
4022075000	75,0	1,8	78,6	118	20,0	50	0,400	20/30/50/100
4022100000	102,0	2,2	106,4	160	12,0	30	0,640	20/30/50/100

Application: High-quality textile braided, flat collapsible, very flexible, lightweight water supply and discharge hose that is frequently used in firefighting, irrigation in agriculture and gardening, shipping, department of defense and many other industrial applications. Hose is extremely wear-resistant due to the cover that is treated with a special wear-resistant coating. Inner wall is seawater resistant and resistant to various chemicals.

Remark:

- Cutted length possible

We recommend assembly with

5110
Storz couplings

