



SPDA-15/SPDA-16 - Compressor

Spare parts dampers

SPDA-15 Small and flexible garage compressor suitable for smaller air machines, cleaning and the like. The compressor has a straight, single-stage direct-drive block with cast iron cylinder. Equipped with pressure switch, overload protection with auto reset, reduction and pressure gauge. Technical data: Voltage 230 V 1-phase. Fuse 10 A. Engine power 2 hp. RPM 2800 rpm. Free avg. air 185 l / min. Max working pressure 8 bar. Block type Straight. Number of steps 1 pc. Cylinders 1 pc. Air outlet 1 pc. Tank 24 liters. Noise level at 7 meters 76 dB (A). Dimensions (lxwxh) 580x280x615 mm. Weight 25 kg.

SPDA-16 Belt driven compressor equipped with a low-speed, two-cylinder compressor block, Abac B2800B, with cast iron cylinders and aftercooling. Comes mounted and finished on one wheeled 50-liter tank with pressure switch, overload protection and reduction. Suitable for the garage and smaller workshops. Voltage 230 V 1-phase, Fuse 10 A, Motor power 3 hp, Speed 1200 rpm. Free avg. air 275 l / min. Max working pressure 10 bar. Block type Straight, Abac B2800B. Number of steps 1 pcs Cylinders 2 pcs. Air outlet 2 pcs. Tank 50 l. Sound level 86 dB (A). Dimensions (lxwxh). 830x380x720 mm. Weight 53 kg.



SPDA-15 - Air compressor 2 hk



SPDA-16 - Air compressor 3 hk

Art.no	Weight (kg)
SPDA-15	25
SPDA-16	53

