

Sweeper hose, medium-heavy, exterior folds, very flexible

Application

- municipal vehicle: sweeper, sweeping machine

Properties

- medium-heavy duty
- highly flexible + compressible
- highly abrasion resistant
- protected, flow-optimizing exterior folds
- microbe resistant

- good resistance to oil, gasoline and chemicals
- very good low temperature flexibility
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40° C to 90° C

Design

- AIRDUC® profile hose

- spring steel wire firmly embedded in wall
- wall: special premium polyurethane (Pre-PUR®)
- wall thickness 1,0 mm approx.

Delivery variants

- further diameters and lengths available on request
- transparent + partially black coloured (standard)
- special colours: partially coloured, completely coloured
- customer-specific branding

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	
partially black coloured							
5,5 / 140	149.00	0,495	0,085	94.00	1.55	5 10	351-0140-5200
6 / 150-152	159.00	0,460	0,075	100.00	1.75	5 10	351-0150-5200
6,3 / 160	169.00	0,435	0,065	106.00	1.95	5 10	351-0160-5200
- / 170	179.00	0,410	0,065	110.00	2.20	5 10	351-0170-5200
7 / 178-180	189.00	0,385	0,055	118.00	2.40	5 10	351-0180-5200
8 / 200-203	211.00	0,350	0,055	130.00	2.40	5 10	351-0200-5200
- / 250	259.00	0,280	0,020	160.00	2.95	5 10	351-0250-5200
transparent							
5,5 / 140	149.00	0,495	0,085	94.00	1.55	5 10	351-0140-2040
6 / 150-152	159.00	0,460	0,075	100.00	1.75	5 10	351-0150-2040
6,3 / 160	169.00	0,435	0,065	106.00	1.95	5 10	351-0160-2040
- / 170	179.00	0,410	0,065	110.00	2.20	5 10	351-0170-2040
7 / 178-180	189.00	0,385	0,055	118.00	2.40	5 10	351-0180-2040
8 / 200-203	211.00	0,350	0,055	130.00	2.40	5 10	351-0200-2040
- / 250	259.00	0,280	0,020	160.00	2.95	5 10	351-0250-2040


Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20° C and are approx. data. Additional information at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20° C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CONNECT 270-271



CONNECT 240 + 241 AS



CLAMP 211