

CLAMP 210 BRIDGE CLAMP



Clamp with plastic bridge for attaching externally corrugated spiral hoses

Properties

- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted
- re-usable

Design

- multi-piece
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Design

- Bridge: PA6
Quality: W1; clamp strip: galvanised steel; screw: galvanised steel; body: galvanised steel

Delivery variants

- 10 pieces plastic bridge with 10 pieces CLAMP 208 loosely welded in a bag
- silver

Suitable for Hose I.D.	Band Width	PU	Order No.
(mm)	(mm)	(Pcs)	
25-31	9	10	210-0025-0000
32-39	9	10	210-0032-0000
40-49	9	10	210-0040-0000
50-59	9	10	210-0050-0000
60-69	9	10	210-0060-0000
70-79	9	10	210-0070-0000
80-89	9	10	210-0080-0000
90-99	9	10	210-0090-0000
100-109	9	10	210-0100-0000
110-119	9	10	210-0110-0000
120-129	9	10	210-0120-0000
130-139	9	10	210-0130-0000
140-149	9	10	210-0140-0000
150-159	9	10	210-0150-0000
160-169	9	10	210-0160-0000
170-179	9	10	210-0170-0000
180-189	9	10	210-0180-0000
190-199	9	10	210-0190-0000
200-209	9	10	210-0200-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

CLAMP 210 BRIDGE CLAMP



CONNECT 270-271



CONNECT 228