

# CLAMP 212 EC



Bridge clamp for attaching externally corrugated spiral hoses

## Properties

- grounding without exposing spiral and without damaging hose
- practically leak-proof and secure clamping with special bridge geometry
- easily and quickly fitted

- re-usable

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

## Design

- Quality: W2; clamp strip: stainless steel 1.4301 = AISI 304; screw: galvanised steel; Body: stainless steel 1.4016 = AISI 430; bridge: stainless steel 1.4301 = AISI 304 (INOX)

## Delivery variants

- further diameters available on request

Suitable for Hose I.D.	Clamping Range	Band Width	Order No.
(mm)	(mm)	(mm)	
-	-	-	-
<b>Clamp with earthing wire</b>			
38-45	35-55	9	212-0035-2878
50-55	45-65	9	212-0045-2878
60-65	55-75	9	212-0055-2878
70-75	65-85	9	212-0065-2878
80-85	75-95	9	212-0075-2878
90-95	85-105	9	212-0085-2878
100-105	95-115	9	212-0095-2878
110-115	105-125	9	212-0105-2878
120-127	115-135	9	212-0115-2878
130-135	125-145	9	212-0125-2878
140-145	135-155	9	212-0135-2878
150-155	145-165	9	212-0145-2878
160-165	155-175	9	212-0155-2878
170-175	165-185	9	212-0165-2878
190-195	185-205	9	212-0185-2878
200-205	195-215	9	212-0195-2878
210-215	205-225	12	212-0205-2878
220-225	215-235	12	212-0215-2878
250-255	245-265	12	212-0245-2878
270-275	265-285	12	212-0265-2878
280-285	275-295	12	212-0275-2878
300-305	295-315	12	212-0295-2878
320-325	315-335	12	212-0315-2878
350-355	345-365	12	212-0345-2878
380-385	375-395	12	212-0375-2878
400-405	395-415	12	212-0395-2878
450-455	445-465	12	212-0445-2878
500-505	495-515	12	212-0495-2878

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

## CLAMP 212 EC

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

## Accessories



CONNECT 270-271

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)