



ry tube support based on DIN 2826/11851

Application

- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- vacuum conveying equipment, vacuum hopper, suction conveyor, dosing system
- pelleting machines/ tablet presses

Properties

- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40 °C to 90 °C

Design

- fitting: stainless steel 1.4301 (stamped) = AISI 304 or 1.4571 (stamped) = AISI 316Ti
- Threaded adapter with light blue Nitrile Perbunan (NBR) seal, safe for food

Delivery variants

- further diameters available on request
- gas and liquid tight as pre-fitted version

Size (mm)	I.D. D1 (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
Thread adapter DIN 2826/11851; stainless steel 1.4301 (stamped) = AISI 304; (please select the hose and the assembly separately)				
25	21.00	0,27	ø 25	247-0025-2912
32	28.00	0,31	ø 32	247-0032-2912
38	33.00	0,35	ø 38	247-0038-2912
40	35.00	0,38	ø 40	247-0040-2912
50	44.90	0,5	ø 50	247-0050-2912
65	58.00	0,85	ø 65	247-0065-2912
75	69.60	0,96	Ø 75	247-0075-2912
80	73.00	1,07	ø 80	247-0080-2912
100	93.50	1,41	ø 100	247-0100-2912
Thread adapter DIN 2826/11851; stainless steel 1.4571 (stamped) = AISI 316Ti; (please select the hose and the assembly separately)				
25	21.00	0,27	ø 25	247-0025-2913
32	28.00	0,31	ø 32	247-0032-2913
38	33.00	0,35	ø 38	247-0038-2913
40	35.00	0,38	ø 40	247-0040-2913
50	44.90	0,5	ø 50	247-0050-2913
65	58.00	0,85	ø 65	247-0065-2913
75	69.60	0,96	Ø 75	247-0075-2913
80	73.00	1,07	ø 80	247-0080-2913
100	93.50	1,41	ø 100	247-0100-2913
tapered adapter DIN 2826/11851; stainless steel 1.4301 (stamped) = AISI 304; (please select the hose and the assembly separately)				
25	21.00	0,36	ø 25	247-0025-2910
32	28.00	0,44	ø 32	247-0032-2910
38	33.00	0,51	ø 38	247-0038-2910
40	35.00	0,6	ø 40	247-0040-2910
50	44.90	0,84	ø 50	247-0050-2910
65	58.00	1,47	ø 65	247-0065-2910

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

CONNECT DAIRY FITTING 247



Size	I.D. D1	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(kg/pcs)	(mm)	
75	69.60	1,75	Ø 75	247-0075-2910
80	73.00	1,95	ø 80	247-0080-2910
100	93.50	2,67	ø 100	247-0100-2910
tapered adapter DIN 2826/11851; stainless steel 1.4571 (stamped) = AISI 316Ti; (please select the hose and the assembly separately)				
25	21.00	0,36	ø 25	247-0025-2911
32	28.00	0,44	ø 32	247-0032-2911
38	33.00	0,51	ø 38	247-0038-2911
40	35.00	0,6	ø 40	247-0040-2911
50	44.90	0,84	ø 50	247-0050-2911
65	58.00	1,47	ø 65	247-0065-2911
75	69.60	1,75	Ø 75	247-0075-2911
80	73.00	1,94	ø 80	247-0080-2911
100	93.50	2,67	ø 100	247-0100-2911

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CONNECT SAFETY CLAMP ASSEMBLY 231



CONNECT MOULD ASSEMBLY 233



CONNECT PRESS ASSEMBLY 232

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/