

CONNECT KARDAN 254



Kardan coupling

Application

- construction industry: lowering groundwater
- for conveying of dry media and liquids

Properties

- Not to be used for explosive fluids group 1 and not according to pressure equipment directive
- REACH according to --> Technology / Technical Information / REACH

Design

- material: galvanized steel
- incl. sealing ring made of NBR

Size (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
female part			
50	1,252	51	254-0050-8211
89	4,00	76	254-0075-8211
108	5,45	102	254-0100-8211
133	7,18	127	254-0125-8211
159	16,57	152	254-0150-8211
male part			
50	0,497	51	254-0050-8411
89	1,110	76	254-0075-8411
108	1,434	102	254-0100-8411
133	2,50	127	254-0125-8411
159	3,600	152	254-0150-8411

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/