

CONNECT STORZ DIN ALU 251



Storz suction coupling

Application

- construction industry: lowering groundwater
- wood pellet heating system: conveying of wood pellets

Properties

- DIN design - forged aluminium (52-C = DIN 14321 / 75-B = DIN 14322 / 110-A = DIN 14323)
- Not to be used for explosive fluids group 1 and not according to pressure equipment directive

- Not to be used for explosive fluids group 1 and not according to pressure equipment directive
- REACH according to --> Technology / Technical Information / REACH

Size (mm)	Lug Spacing (mm)	Weight (kg/pcs)	Suitable for Hose I.D. (mm)	Order No.
replacement seal NBR back				
52-C	66	0,02	-	251-0052-8068
75-B	89	0,03	-	251-0075-8068
110-A	133	0,05	-	251-0110-8068
with corrugated nozzle for band clamp fitting; suitable to CONNECT 229 CLAMP ASSEMBLY				
52-C	66	0,35	50	251-0050-8012
75-B	89	0,66	75	251-0075-8012
110-A	133	1,84	100	251-0100-8012
with smooth nozzle and locking ring for clamp shell band fitting; suitable to CONNECT 231 SAFETY CLAMP ASSEMBLY				
52-C	66	0,35	50	251-0050-8022
75-B	89	0,66	75	251-0075-8022
110-A	133	1,84	100	251-0100-8022

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CLAMP 211

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/