



Shrink sleeve for connecting one hose to another or to an adapter

Properties

- adapts itself to any surface
- easily and quickly fitted
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40° C to 125° C

Design

- polyolefine

Delivery variants

- further diameters available on request
- black (standard)

| Shrinking Range | Total Length | Suitable for Hose I.D. | Order No. |
|-----------------|--------------|------------------------|---------------|
| (mm) | (mm) | (mm) | |
| 15-30 | 70 | 15-22 | 223-0038-0000 |
| 22-50 | 80 | 20-40 | 223-0050-0000 |
| 25-63 | 80 | 30-50 | 223-0063-0000 |
| 30-75 | 90 | 40-60 | 223-0075-0000 |
| 35-85 | 100 | 50-70 | 223-0085-0000 |
| 40-95 | 110 | 60-80 | 223-0095-0000 |
| 45-115 | 120 | 80-100 | 223-0115-0000 |
| 50-140 | 150 | 100-130 | 223-0140-0000 |
| 60-160 | 170 | 130-150 | 223-0160-0000 |
| 70-180 | 190 | 150-170 | 223-0180-0000 |

Muffenlänge: 1m

| | | | |
|--------|------|---------|---------------|
| 15-30 | 1000 | 15-22 | 223-0038-9001 |
| 22-50 | 1000 | 20-40 | 223-0050-9001 |
| 25-63 | 1000 | 30-50 | 223-0063-9001 |
| 30-75 | 1000 | 40-60 | 223-0075-9001 |
| 35-85 | 1000 | 50-70 | 223-0085-9001 |
| 40-95 | 1000 | 60-80 | 223-0095-9001 |
| 45-115 | 1000 | 80-100 | 223-0115-9001 |
| 50-140 | 1000 | 100-130 | 223-0140-9001 |
| 60-160 | 1000 | 130-150 | 223-0160-9001 |
| 70-180 | 1000 | 150-170 | 223-0180-9001 |

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20° C and are approx. data. Additional information at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20° C and are approx. data. Additional information at www.norres.com/en/technology/

CONNECT 223

Accessories



CLAMP 208



CONNECT 270-271