



## Soft sleeve for SuperFlex hoses

### Application

- industrial vacuum cleaners, vacuum cleaners

### Properties

- easily and quickly fitted
- re-usable (threaded version)
- good resistance to alkalis and acids

- good resistance to chemicals
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- -20 °C to 70 °C
- short time to 80 °C

### Design

- wall: high grade soft PVC

### Delivery variants

- further diameters available on request
- black (standard)

Rec. Adapter Ø	Rec. Adapter length	Threading depth Hose	Total Length	Weight	Suitable for Hose I.D.	Order No.
(mm)	(mm)	(mm)	(mm)	(kg/pcs)	(mm)	
<b>Suitable for hose 372-.....0000</b>						
25	50	45	100	0,050	25	226-0025-0000
32	50	45	100	0,060	32	226-0032-0000
38	50	45	100	0,070	38	226-0038-0000
41	50	45	100	0,070	41	226-0041-0000
44	50	45	100	0,080	44	226-0044-0000
51	50	45	100	0,090	51	226-0051-0000
63	50	45	100	0,130	63	226-0063-0000
70	45	45	100	0,150	70	226-0070-0000
76	45	45	100	0,170	76	226-0076-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)