



Elastic clamp protection tape

Properties

- easily and quickly fitted
- re-usable
- highly abrasion resistant
- good resistance to oil, gasoline and chemicals
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- -40° C to 90° C
- short time to 125° C

Design

- wall: polyurethane

- wall: polyurethane

Delivery variants

- further diameters available on request
- black (standard)
- special colours: full coloured

Suitable for Hose I.D. (mm)	Order No.
1,5 / 38	228-0038-0000
2 / 50-51	228-0050-0000
2,36 / 60	228-0060-0000
2,5 / 63-65	228-0063-0000
3 / 75-76	228-0075-0000
3,5 / 89-90	228-0090-0000
4 / 100-102	228-0100-0000
4,5 / 114-115	228-0115-0000
5 / 125-127	228-0125-0000
6 / 150-152	228-0150-0000
6,3 / 160	228-0160-0000
6,5 / 165	228-0165-0000
7 / 178-180	228-0180-0000
8 / 200-203	228-0200-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20° C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CONNECT 270-271



CLAMP 212

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20° C and are approx. data. Additional information at www.norres.com/en/technology/