


CONNECT 270-271



Metal hose connector / reducer

Properties

- easily and quickly fitted
- re-usable (threaded version)
- conforms to RoHS guideline

- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- 200 °C

Design

- galvanised sheet metal

Delivery variants

- further diameters available on request
- Stainless Steel (INOX)

Suitable for Hose Ø-D1 (mm)	Suitable for Hose Ø-D2 (mm)	Adapter length L1 (mm)	Adapter length L2 (mm)	Total Length (mm)	Wall Thickness (mm)	Weight (kg/pcs)	Order No.
Hose connector							
50	50	40	40	L3: 90	0.60	0,200	270-0050-0000
60	60	40	40	L3: 90	0.60	0,200	270-0060-0000
70	70	40	40	L3: 90	0.60	0,200	270-0070-0000
75	75	40	40	L3: 90	0.60	0,200	270-0075-0000
80	80	40	40	L3: 90	0.60	0,200	270-0080-0000
90	90	40	40	L3: 90	0.60	0,200	270-0090-0000
100	100	40	40	L3: 90	0.60	0,200	270-0100-0000
110	110	40	40	L3: 90	0.60	0,300	270-0110-0000
120	120	40	40	L3: 90	0.60	0,300	270-0120-0000
125	125	40	40	L3: 90	0.60	0,300	270-0125-0000
130	130	40	40	L3: 90	0.60	0,300	270-0130-0000
140	140	40	40	L3: 90	0.60	0,400	270-0140-0000
150	150	40	40	L3: 90	0.60	0,500	270-0150-0000
160	160	40	40	L3: 90	0.60	0,500	270-0160-0000
170	170	40	40	L3: 90	0.60	0,500	270-0170-0000
175	175	40	40	L3: 90	0.60	0,600	270-0175-0000
180	180	40	40	L3: 90	0.60	0,600	270-0180-0000
200	200	40	40	L3: 90	0.60	0,600	270-0200-0000
215	215	40	40	L3: 90	0.60	0,700	270-0215-0000
225	225	40	40	L3: 90	0.60	0,700	270-0225-0000
250	250	60	60	L3: 130	0.60	0,800	270-0250-0000
275	275	60	60	L3: 130	0.60	0,900	270-0275-0000
300	300	60	60	L3: 130	0.70	1,000	270-0300-0000
315	315	60	60	L3: 130	0.70	1,100	270-0315-0000
325	325	60	60	L3: 130	0.70	1,200	270-0325-0000
350	350	60	60	L3: 130	0.70	1,300	270-0350-0000
375	375	80	80	L3: 170	0.70	1,500	270-0375-0000
400	400	80	80	L3: 170	0.70	1,600	270-0400-0000
450	450	80	80	L3: 170	0.70	2,100	270-0450-0000
500	500	80	80	L3: 170	0.70	2,300	270-0500-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

CONNECT 270-271


Suitable for Hose Ø-D1 (mm)	Suitable for Hose Ø-D2 (mm)	Adapter length L1 (mm)	Adapter length L2 (mm)	Total Length (mm)	Wall Thickness (mm)	Weight (kg/pcs)	Order No.
Hose reduction							
75	50	40	40	L3: 135	0.60	0,200	271-0075-0000
80	70	40	40	L3: 125	0.60	0,200	271-0080-0000
80	50	40	40	L3: 135	0.60	0,200	271-0080-2655
100	80	40	40	L3: 140	0.60	0,200	271-0100-0000
100	70	40	40	L3: 150	0.60	0,200	271-0100-2660
125	100	40	40	L3: 145	0.60	0,300	271-0125-0000
125	80	40	40	L3: 175	0.60	0,300	271-0125-2665
150	100	40	40	L3: 175	0.60	0,300	271-0150-0000
150	80	40	40	L3: 205	0.60	0,400	271-0150-2670
150	125	40	40	L3: 145	0.60	0,300	271-0150-2671
200	150	40	40	L3: 175	0.60	0,500	271-0200-0000
200	100	40	40	L3: 245	0.60	0,600	271-0200-2675
200	125	40	40	L3: 215	0.60	0,600	271-0200-2676
250	200	60	40	L3: 200	0.60	0,800	271-0250-0000
250	125	60	40	L3: 300	0.60	1,000	271-0250-2680
250	150	60	40	L3: 270	0.60	0,900	271-0250-2681
300	200	60	40	L3: 265	0.70	1,200	271-0300-0000
300	150	60	40	L3: 335	0.70	1,300	271-0300-2685
300	250	60	40	L3: 195	0.70	1,300	271-0300-2687

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CLAMP 217



CONNECT 228



CLAMP 212



CLAMP 211

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at www.norres.com/en/technology/