



Abrasion resistant polyurethane hose/ tubing, fabric reinforced pressure hose

Application

- flexible hose/ ducting for liquids and for gases and for abrasive solids
- food industry, pharmaceutical industry: foodstuff, pharmaceutical
- conveying of dry foods e.g. rice, cereals, sugar, milk powder, powders, coffee, tea, grains, flour, frozen foods
- injection moulding tool cooling, cooling water supply
- powder spraying, powder coating: e.g. printing industry
- industrial washing machine: washing water hose
- compressed air hose, cooling water hose, water hose
- fabric reinforced hose/ braided hose
- heating hose: interior hose for media transfer

Properties

- fabric reinforced

- highly flexible
- highly abrasion resistant
- crush resistant
- Food grade wall, complies with: EU-Directive 10/2011 and EC 1935/2004 and the latest EU-Directive 2015/174
- odourless and tasteless
- microbe and hydrolysis resistant
- good resistance to oil, gasoline and chemicals
- very good low temperature flexibility
- manufacturing process acc. GMP EC 2023/2006
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

Temperature Range

- 40°C to 90°C
- short time to 125°C

Design

- NORFLEX® design
- fabric reinforced wall
- smooth interior and exterior
- wall: special premium ether-polyurethane (Pre-PUR®)

Delivery variants

- further diameters and lengths available on request
- transparent (standard)
- special colours: full coloured
- customer-specific branding

I.D.	outer Ø	Wall Thickness	Pressure	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	mm	(bar)	(mm)	(kg/m)	(m)	(m)	
1/8 / 2,9	5.70	1.40	20,000	14.00	0.02	50	-	441-9029-0000
- / 4	8.00	2.00	20,000	13.00	0.05	50	-	441-9040-0000
1/4 / 6	10.00	2.00	16,000	22.00	0.06	50	-	441-9060-0000
1/4 / 6	12.00	3.00	20,000	22.00	0.10	-	50	441-9060-2175
- / 6,5	10.00	1.80	16,000	22.00	0.05	-	50	441-9065-0000
- / 7	10.00	1.50	14,000	27.00	0.05	-	50	441-9070-0000
5/16 / 8	12.00	2.00	16,000	26.00	0.08	50	-	441-9080-0000
- / 8,5	12.50	2.00	16,000	36.00	0.08	-	50	441-9085-0000
3/8 / 9,5	13.50	2.00	14,000	45.00	0.09	50	-	441-9095-0000
3/8 / 10	14.50	2.30	12,000	55.00	0.10	50	-	441-9100-0000
- / 11	16.00	2.50	12,000	55.00	0.13	-	50	441-9110-0000
1/2 / 13	19.00	3.00	10,000	79.00	0.18	50	-	441-9130-0000
3/4 / 19	25.00	3.00	8,000	116.00	0.25	50	-	441-9190-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at www.norres.com/en/technology/

Accessories



CLAMP 208