



PVC hose, light

### Application

- flexible hose/ ducting for gases and for dust, powder, fibres
- extraction unit, dedusting system, filter system, oil mist extraction
- galvanic extraction
- chemical industry: chemical vapours, vapour return hose at loading arm, paint steam, spray mist extraction
- X-ray machine: cable protection conduit (special type on request)
- heating hose: exterior hose as protection hose

### Properties

- light weight
- highly flexible + compressible 3:1

- good resistance to alkalis and acids
- good resistance to chemicals
- phthalate-free
- flame-retardant according to: UL94-HB
- conforms to RoHS guideline
- REACH according to --> Technology / Technical Information / REACH

### Temperature Range

- 20 °C to 70 °C
- short time to 80 °C

### Design

- patented PROTAPE® tape hose
- spring steel wire integrated in wall
- wall: high grade soft PVC
- wall thickness 0,5 mm approx.

### Delivery variants

- further diameters and lengths available on request
- grey (standard)
- special colours: transparent, full coloured
- customer-specific branding
- ID >= 2"/50-51mm compressed packed in poly bag (low transportation cost / risk, minimum storage size), ID < 2"/50-51mm not compressed, wrapped in a coil

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
- / 30	37.00	0,930	0,200	22.00	0.24	5 10 15	-	310-0030-0000
1,25 / 32	39.00	0,875	0,200	23.00	0.26	5 10 15	-	310-0032-0000
1,5 / 38	45.00	0,740	0,185	26.00	0.30	5 10 15	-	310-0038-0000
- / 40	47.00	0,705	0,180	27.00	0.32	5 10 15	-	310-0040-0000
2 / 50-51	58.00	0,410	0,155	33.00	0.31	5 10 15	-	310-0050-0000
- / 55	63.00	0,370	0,140	36.00	0.33	5 10 15	-	310-0055-0000
2,36 / 60	68.00	0,340	0,120	38.00	0.36	5 10 15	-	310-0060-0000
2,5 / 63-65	73.00	0,315	0,105	41.00	0.39	5 10 15	-	310-0065-0000
- / 70	78.00	0,295	0,090	43.00	0.42	5 10 15	-	310-0070-0000
3 / 75-76	83.00	0,275	0,085	46.00	0.45	5 10 15	-	310-0075-0000
- / 80	88.00	0,255	0,075	48.00	0.47	5 10 15	-	310-0080-0000
3,5 / 89-90	98.00	0,230	0,065	53.00	0.53	5 10 15	-	310-0090-0000
4 / 100-102	108.00	0,205	0,050	58.00	0.57	5 10 15	-	310-0100-0000
- / 110	118.00	0,185	0,045	63.00	0.62	5 10 15	-	310-0110-0000
4,5 / 114-115	123.00	0,180	0,045	66.00	0.65	5 10 15	-	310-0115-0000
4,72 / 120	128.00	0,170	0,045	68.00	0.68	5 10 15	-	310-0120-0000
5 / 125-127	133.00	0,165	0,035	71.00	0.71	5 10 15	-	310-0125-0000
- / 130	138.00	0,160	0,035	73.00	0.73	5 10 15	-	310-0130-0000
5,5 / 140	148.00	0,145	0,035	78.00	0.79	5 10 15	-	310-0140-0000
6 / 150-152	158.00	0,135	0,035	83.00	0.84	5 10 15	-	310-0150-0000
6,3 / 160	168.00	0,130	0,030	88.00	0.87	5 10 15	-	310-0160-0000
7 / 178-180	188.00	0,115	0,025	98.00	1.00	5 10 15	-	310-0180-0000
8 / 200-203	208.00	0,105	0,025	108.00	1.11	5 10	-	310-0200-0000
- / 225	233.00	0,090	0,015	121.00	1.25	5 10	-	310-0225-0000

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20 °C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

I.D.	outer Ø	Pressure	Vacuum	Bending Radius	Weight	Dimensions in Stock	Production Lengths	Order No.
(in / mm)	(mm)	(bar)	(bar)	(mm)	(kg/m)	(m)	(m)	
- / 250	258.00	0,085	0,010	133.00	1.39	<b>5 10</b>	-	310-0250-0000
- / 300	309.00	0,070	0,010	159.00	1.95	<b>5 10</b>	-	310-0300-0000

**Sondertyp DB.P1: größere Steigung, höhere Stauchbarkeit, 0.4mm Wandstärke, weniger Gewicht, Lagerware nur in Italien**

- / 30	34.00	0,850	0,140	0.00	0.14	<b>10</b>	5 6 15 20	310-0030-2025
- / 40	44.00	0,645	0,105	0.00	0.18	<b>10</b>	5 6 15 20	310-0040-2025
2 / 50-51	54.00	0,515	0,086	0.00	0.23	<b>10</b>	5 6 15 20	310-0050-2025
2,36 / 60	64.00	0,430	0,072	0.00	0.27	<b>10</b>	5 6 15 20	310-0060-2025
2,5 / 63-65	69.00	0,400	0,065	0.00	0.29	<b>10</b>	5 6 15 20	310-0065-2025
- / 70	74.00	0,370	0,060	0.00	0.32	<b>10</b>	5 6 15 20	310-0070-2025
3 / 75-76	79.00	0,345	0,060	0.00	0.34	<b>10</b>	5 6 15 20	310-0075-2025
- / 80	84.00	0,325	0,055	0.00	0.36	<b>10</b>	5 6 15 20	310-0080-2025
3,5 / 89-90	94.00	0,290	0,050	0.00	0.40	<b>10</b>	5 6 15 20	310-0090-2025
4 / 100-102	104.40	0,260	0,045	0.00	0.38	<b>10</b>	5 6 15 20	310-0100-2025
- / 110	114.40	0,240	0,040	0.00	0.41	<b>10</b>	5 6 15 20	310-0110-2025
4,72 / 120	124.40	0,220	0,035	0.00	0.45	<b>10</b>	5 6 15 20	310-0120-2025
5 / 125-127	129.40	0,220	0,035	0.00	0.47	<b>10</b>	5 6 15 20	310-0125-2025
- / 130	134.40	0,200	0,033	0.00	0.49	<b>10</b>	5 6 15 20	310-0130-2025
5,5 / 140	144.40	0,185	0,030	0.00	0.56	<b>10</b>	5 6 15 20	310-0140-2025
6 / 150-152	154.40	0,175	0,030	0.00	0.56	<b>10</b>	5 6 15 20	310-0150-2025
6,3 / 160	164.40	0,165	0,030	0.00	0.60	<b>10</b>	5 6 15 20	310-0160-2025
7 / 178-180	184.40	0,145	0,025	0.00	0.67	<b>10</b>	5 6 15 20	310-0180-2025
8 / 200-203	204.80	0,130	0,022	0.00	0.72	<b>10</b>	5 6 15	310-0200-2025
- / 225	229.80	0,115	0,019	0.00	0.81	<b>10</b>	5 6 15	310-0225-2025
- / 250	254.80	0,105	0,018	0.00	0.90	<b>10</b>	5 6 15	310-0250-2025
- / 275	279.80	0,095	0,016	0.00	0.90	<b>10</b>	5 6 15	310-0275-2025
- / 300	304.80	0,090	0,015	0.00	1.08	<b>10</b>	5 6 15	310-0300-2025
- / 350	355.20	0,075	0,012	0.00	1.36	<b>10</b>	5 6	310-0350-2025
- / 400	405.60	0,065	0,011	0.00	1.50	-	5 6	310-0400-2025
- / 450	455.60	0,060	0,010	0.00	1.82	-	5 6	310-0450-2025
- / 500	505.60	0,050	0,009	0.00	2.02	-	5 6	310-0500-2025

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)

## Accessories



CONNECT 228



CLAMP 217



CLAMP 210 BRIDGE CLAMP



CONNECT 270-271



CLAMP 213



CONNECT 223



CLAMP 212

Overpressure and underpressure are recommended threshold operating values, products can be subjected to higher loads upon request. The bending radius is measured through the inside of the hose arch. The right to make technical modifications is reserved. All values determined at 20°C and are approx. data. Additional information at [www.norres.com/en/technology/](http://www.norres.com/en/technology/)