

European Headquarters

Tiger-Vac Europa S.R.L. Via Marie Curie 17 Zona Industriale Ponte Rizzoli Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077) Website: http://www.tiger-vac.eu Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2

Tel: (450-625-0099) Fax: (450-625-3388) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com



ATEX

C€ 🔂 II 2GD Ex h IIC T6 Gb Ex h IIIC T85°C Db



Static HEPA Dissipating Included



High Filtration Efficiency Unit



Stainless

General

SD Accessories



Wet and Dry - Included Recovery

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards.

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

Specifications for ATEX-12A (4W)

•					
Name	Part Number	Air Flow		Vacuum Pressure	Dry Recovery - Tank
ATEX-12A (4W)	111962	187 m ³ /h		2790 mm H ₂ 0	38 L
	Dimensions: H81 cm x W48	cm x L52 cm	Weight: 11	.3 kg. Sound Level: 68 dE	B(A)
Description: Specifications may vary depending upon performance of the compressor.					

Please note that specifications are subject to change without notice

Technical Sheet for ATEX-12A (4W)

HEPA FILTER AND ACCESSORIES - Included		
Part #	Description	
212304B-HD	HEPA FILTER, 99.99% EFFICIENCY ON 0.3 MICRON, HEAVY DUTY CONSTRUCTION	

FILTERS AN	ILTERS AND ACCESSORIES - Included	
Part #	Description	
211430T	MAIN FILTER ASSEMBLY, PTFE LAMINATED, W/YELLOW GASKET, W/RING #214279 FOR USE WITH POLY TANKS	
211394	LIQUID FILTER ASSEMBLY	

TOOLS AN	OOLS AND ACCESSORIES - Included	
Part #	Description	
383440B	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY(NO WIRE) 1.5"(38mm) x 10'(3m) FOR 2" CAMLOCK INTAKE	
211029C	AIR SUPPLY HOSE ASMBLY SD* Ø0.5"(12.7mm)x25'(7.5m) WITH MALE NPT ON ONE END & CHICAGO ON OTHER END	
381208	CURVED HANDLE, 1.5" TO 1.25" (38mm TO 32mm), CHROME, WITH BUTTON LOCK & AIRFLOW REGULAR	
323315	EXTENSION WANDS, 1.25" (32mm) SET OF 2, CHROME WITH HOLE FOR BUTTON LOCK	
323318A	UTILITY FLOOR TOOL, Ø1.25"(Ø32mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES	
323317A	UTILITY FLOOR TOOL, 1.25"(Ø32mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/GREY SQUEEGEE BLADES	
323312A	ROUND BRUSH, 1.25"(32mm) x 3"(7.5cm), ESD SAFE PLASTIC, WITH HOLE FOR BUTTON LOCK	
323313A	CREVICE TOOL, 1.25"(32mm) x 8"(20cm), BLACK, ESD SAFE PLASTIC w/HOLE FOR BUTTON LOCK	
323314A	UPHOLSTERY FLAT TOOL, 1.25"(32mm) x 5"(13cm), ESD SAFE PLASTIC	

TOOLS AN	FOOLS AND ACCESSORIES - Optional	
Part #	Description	
383438-50	CRUSHPROOF SUCTION HOSE, BLACK STATIC CONDUCTIVE (NO WIRE),Ø1.5" (Ø38mm) x 50'	
383434	HOSE CUFF UNION WITH SWIVEL Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK	
383436	HOSE CUFF Ø1.5"(38mm) STATIC CONDUCTIVE -BLACK	
383435	EXPANDER HOSE CUFF, 1.5"(38mm) HOSE TO 2"(50mm) TUBE, STATIC CONDUCTIVE, BLACK	
500175	CAMLOCK SPECIAL PART C Ø2"(50mm)FEMALE ADAPTOR TO Ø1.5"(38mm)HOSE SHANK -ALUMINUM	
381477	DOUBLE BEND WAND (2pc) 1.5" (38mm) x 54" (137cm), CHROME, w/TAPER FOR PLASTIC FLOOR TOOLS	

381448A	UTILITY FLOOR TOOL, Ø1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/CONDUCTIVE NYLON BRISTLES
381447A	UTILITY FLOOR TOOL, 1.5"(Ø38mm) x 12"(30cm), STATIC CONDUCTIVE PLASTIC w/GREY SQUEEGEE BLADES
381155A	REDUCER, TAPERED 1.5"(38mm) TO 1.25"(32mm) ALUMINUM SD* (WITHOUT ANODIZED)

PRESSURE	ESSURE REGULATOR - Optional	
Part # Description		
219841	GENERAL PURPOSE AIR PRESSURE REGULATOR, 0.5" NPT PORTS (NB: Pressure regulator only - not a filter)	