

**European Headquarters** 

Tel: ((39) 051 79.53.52) Fax: ((39) 051 4695077) Website: http://www.tiger-vac.eu Email: info@tiger-vac.it

## **International Headquarters**

Tiger-Vac International Inc. 2020 Dagenais Blvd. Ouest Laval, Quebec Canada H7L 5W2

Tel: (450-625-0099) Fax: (450-625-3388) Website: http://www.tiger-vac.com Email: sales@tiger-vac.com



Tiger-Vac Europa S.R.L.

Ozzano Emilia, BO 40064

Via Marie Curie 17 Zona Industriale Ponte Rizzoli

**ATEX** 

CE 😉 II 3D Ex tc IIIC T135°C Dc IP64

ESD Safe Vacuum Systems for Hazardous

We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic



Dry Recovery





Detachable Tank



Optional

Static Dissipating

Locations are designed to prevent ignition hazards.

Discharge (ESD)

This model can be used to Recover Combustible Dusts such as Dust Groups: IIIA Combustible Flyings (lints of cotton, wood chips, etc.)



IIIB Non-Conductive Dusts (flour dust, grain dust, flour, sugar, starch, wood, plastic, carbonaceous dusts, coal, carbon black) **IIIC** Conductive Dusts (combustible metal dust, aluminum, magnesium, commercial alloys)

## Specifications for CD-100L (DT) EX (MFS) Z22

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank
CD- 100L	112582B1- Z22	400 V	50 Hz	Three	3400 W	3.4 kW	8 A	306 m <sup>3</sup> /h	2540 mm H <sub>2</sub> 0	Not Included	100 L
(DT) EX (MFS) Z22	Dimensions: H	168 cm x V	V69 cm x L1	117 cm	Weight: 164	1 kg. Sc	ound Level: 72	2 dB(A)			
Description: Certified ATEX 3D											

CD- 100L (DT) EX (MFS) Z22	112586B1- Z22	400 V	50 Hz	Three	5200 W	5.2 kW	10 A	500 m <sup>3</sup> /h	2540 mm H <sub>2</sub> 0	Not Included	100 L
	Dimensions: H168 cm x W69 cm x L117 cm Weight: 164 kg. Sound Level: 75 dB(A)										
Descriptio	cription: Certified ATEX 3GD										

Please note that specifications are subject to change without notice

## Technical Sheet for CD-100L (DT) EX (MFS) Z22

HEPA F	HEPA FILTER AND ACCESSORIES FOR 3.4 kW MODELS - DOWNSTREAM - Optional					
Part #	Description					
212202	HEPA FILTER, 11" HIGH w/GASKET, EFFICIENCY OF 99.995% ON 0.3 MICRON (H14)					

HEPA F	EPA FILTER AND ACCESSORIES FOR 5.2 kW MODELS - DOWNSTREAM - Optional					
Part #	Description					
212202A	HEPA FILTER, 22" HIGH, EFFICIENCY OF 99.99% ON 0.3 MICRON					

FILTERS AND ACCESSORIES - Included				
Part #	Description			
218637	MAIN FILTER ASSEMBLY, SD* PTFE STAR SHAPED (12) FILTER (PLEATED)			

	Ø50mm	mm STATIC CONDUCTIVE SUCTION HOSE ASSEMBLY - Included				
	Part #	Description				
-	500540D	CRUSHPROOF SUCTION HOSE ASSEMBLY 2"(50mm) x 15'(4.5m) STATIC CONDUCTIVE, FOR 2.5" CAMLOCK INTAKE				

Ø50mm	TOOLS AND ACCESSORIES - TOOL KIT # 13 P/N 500113 - CONSISTS OF THE FOLLOWING TOOLS: - Included
Part #	Description
500160	WAND ONLY, SINGLE BEND, 2"(50mm) x 48" (122cm), ALUMINUM, WITH TAPER FOR FLOOR TOOL
	UNIVERSAL TOOL Ø2"(50mm)x20"(51cm)SD* NO COUPLING WITH BRASS WHEELS&CONDUCTIVE BRISTLES&RUBBER BLADE
500156B	CREVICE TOOL SD* (NO COUPLING) Ø2"(50mm)x15"(38cm) -ALUMINUM
501184A	DUSTING BRUSH ALUMINUM SD* Ø2"(50mm)x5"(12.7cm)WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT
500230	CONICAL NOZZLE RUBBER SD* ASSEMBLY Ø2"(50mm)x7.5"(19cm) WITH Ø2"(50mm)PRESSURE FIT ALUM. CONNECTOR