

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



This model can be used to Recover Combustible Dusts such as Dust Groups :
IIIA Combustible Flyings (lints of cotton, wood chips, etc.)
IIIB Non-Conductive Dusts (flour dust, grain dust, flour, sugar, starch, wood, plastic, carbonaceous dusts, coal, carbon black)
IIIC Conductive Dusts (combustible metal dust, aluminum, magnesium, commercial alloys)



Dry Recovery



Continuous Duty



Detachable Tank



Static Dissipating

ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)

ATEX II 3D
Ex tc IIIC T135°C Dc IP64

Specifications for CD-15 (DT) EX (MFS) Z22

Name	Part Number	Voltage	Hertz	Phase	Wattage	Power	Amperage	Air Flow	Vacuum Pressure	Plug Type	Dry Recovery - Tank
CD-15 (DT) EX (MFS) Z22	111221B1-Z22	400 V	50 Hz	Three	2600 W	2.6 kW	8 A	320 m ³ /h	3260 mm H ₂ O	Not Included	55 L
Dimensions: H145 cm x W60 cm x L110 cm Weight: 93 kg. Sound Level: 73 dB(A)											

Please note that specifications are subject to change without notice

Technical Sheet for CD-15 (DT) EX (MFS) Z22

Ø38mm STATIC CONDUCTIVE SUCTION HOSE ASSEMBLY - Optional

Part #	Description
383440D	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY 1.5"(38mm) x 10'(3m)FOR USE w/60mm CONDUCTIVE INLET
383441D	STATIC CONDUCTIVE CRUSHPROOF SUCTION HOSE ASMBLY 1.5"(38mm) x 15'(4.5m)FOR w/60mm CONDUCTIVE INLET

Ø38mm TOOLS AND ACCESSORIES - TOOL KIT # 17 P/N 383551 - CONSISTS OF THE FOLLOWING TOOLS: - Optional

Part #	Description
381163	DOUBLE BEND WAND ASSEMBLY (2pc), 1.5" (38mm) x 54" (137cm), CHROME w/ALUMINUM TOOL COUPLING
381377A	FLOOR TOOL ALUMINUM 1.5"(38mm) x 14"(36cm) WITH CONDUCTIVE BRISTLES
381188	CREVICE TOOL SD*, 1.5" (38mm) x 11" (28cm), ALUMINUM

Ø38mm TOOLS AND ACCESSORIES - Optional

Part #	Description
383462	CONICAL NOZZLE ASMBLY w/CURVED TIP, 10"(25cm) CONDUCTIVE RUBBER, PRESSURE FIT (323562+381155A-H)
381185A	DUSTING BRUSH, SD*, 5"(12.5cm), ALUMINUM w/STAINLESS STEEL COUPLING #381147B, w/CONDUCTIVE BRISTLES

Ø50mm STATIC CONDUCTIVE SUCTION HOSE ASSEMBLY - Optional

Part #	Description
--------	-------------

500710P	CRUSHPROOF HOSE ASMBLY 2"(50mm) X 10'(3m) STATIC CONDUCTIVE w/ROUND CROWN FOR USE w/60mm METAL INLET
---------	--

Ø50mm TOOLS AND ACCESSORIES - Optional	
Part #	Description
500160	WAND ONLY, SINGLE BEND, 2"(50mm) x 48" (122cm), ALUMINUM, WITH TAPER FOR FLOOR TOOL
500161A	UNIVERSAL TOOL Ø2"(50mm)x20"(51cm)SD* NO COUPLING WITH BRASS WHEELS&CONDUCTIVE BRISTLES&RUBBER BLADE
500156B	CREVICE TOOL SD* (NO COUPLING) Ø2"(50mm)x15"(38cm) -ALUMINUM
501184A	DUSTING BRUSH ALUMINUM SD* Ø2"(50mm)x5"(12.7cm)WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT
500230	CONICAL NOZZLE RUBBER SD* ASSEMBLY Ø2"(50mm)x7.5"(19cm) WITH Ø2"(50mm)PRESSURE FIT ALUM. CONNECTOR