

ATEX

ATEX 3rd Party Certified
CE 0081 II 2GD
Ex d IIA T3 Gb
Ex t IIIC T200°C Db IP6X
LCIE 03 ATEX 6297



GUARANTEED for the Safe Recovery of Combustible/Conductive Dusts and Flammable Liquids


ESD Safe Vacuum Systems for Hazardous Locations are designed to prevent ignition hazards. We use metal parts or Static Dissipative Powder Coating to prevent Electrostatic Discharge (ESD)



Characteristics



EX Certified



Less than 10 ohms



HEPA - Included



High Filtration Efficiency Unit



Cleanroom Compatible



Pharma Applications



Wet and Dry Recovery



SS 304



SD Accessories - Included

- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - included
- Cleanroom compatible with ISO Class 4 (former Class 10). Can be used in the Pharmaceutical industry
- For general cleanup in hazardous locations
- Single phase explosion proof/dust ignition proof motor
- For wet & dry recovery
- All stainless steel SAE 304 construction (except cart)
- Stainless steel cart available
- Static dissipative poly liner and clip for the easy and safe disposal of recovered materials - available
- Mounted on a 4-wheel cart for easy maneuverability. Cart has static dissipative wheels
- Includes a complete static dissipative tool kit

Specifications

EXP1-55 (TC) RE SERIES	110333B
Model Name	EXP1-55 (TC) RE HEPA
Type (Powerhead)	Electric
TEFC Motor	Yes
Voltage	230 V
Hertz	50 Hz
Phase	Single
Wattage	1000 W
Power	1 kW
Amperage	4.5 A
Air Flow	224 m ³ /h
Vacuum Pressure	1550 mm H ₂ O
Sound Level	78/85 dB(A)
Plug Type	Not Included
Suction Inlet	50 mm
Cart Type	Tilt Cart (TC)
Filter Cleaning	None
Dry Recovery - Tank	151 L
Liquid Recovery Capacity	170 L
Width	71 cm
Height	127 cm
Weight (Vacuum Only)	70 kg.
Cord Length	15 m

Please note that specifications are subject to change without notice

Use only recommended tools & accessories



Ø1.5 (Ø38 mm) Static Dissipative Tools and Accessories - Included



HEPA Filter - Included



Grounding reel with stainless steel housing and cable - Optional