

ATEX 3rd Party Certified



CE II 2GD

Ex h IIC T6 Gb
Ex h IIIC T85°C Db
LCIE 03 ATEX 6310 X



Ex h IIC T6 Gb
Ex h IIIC T85°C Db
IECEx LCIE 17.0076 X



GUARANTEED for the Safe Recovery of Combustible/Conductive
Dusts and Flammable Liquids

ESD Safe Vacuum Systems for Hazardous Locations are designed
to prevent ignition hazards.


We use metal parts or Static Dissipative Powder Coating to prevent
Electrostatic Discharge (ESD)



Characteristics



EX Certified




Less than 10
ohms




HEPA Filter
Available
HEPA - Optional



Wet Recovery



Activated
Carbon



Hydrocart



Coalescing
Filter Element

- Legally certified explosion proof/dust ignition proof
- Less than 10 ohms of resistivity
- Coalescing Filter Element (CFE) for moisture removal
- HEPA filter with an efficiency of 99.995% at 0.3 micron. Tested IEST-RP-CC001. H14 by MPPS method as per EN 1822 and OSHA compliant. All of our HEPA vacuum systems are aerosol leak tested before leaving our facility - optional
- Pneumatic (air-operated)
- For fuel, oil, and solvent recovery
- Designed for the adsorption of toxic/noxious vapors, fumes and odors
- Activated Carbon (AC) drum system contains 55 lb (25 kg) of activated carbon pellets
- Equipped with a heavy duty powder coated hydraulic cart for easy emptying of recovered material. Cart has static dissipative or conductive wheels

Specifications

SS-25 AC TE (HY-C)	110281
Model Name	SS-25 AC TE (HY-C)
Type (Powerhead)	Pneumatic
Venturi	Single
Venturi (diam.)	6 mm
Minimum Compressor	15 HP
Air Line Size (Diam.)	1/2" (12.7mm)
Input Air Volume	21.2 L/s
Input Air Pressure	5.5 Bar
Air Flow	204 m ³ /h
Vacuum Pressure	4570 mm H ₂ O
Suction Inlet	38 mm
Cart Type	Hydro Cart (HYC)
Filter Cleaning	None
Dry Recovery - Tank	3.8 L
Length	124 cm
Width	51 cm
Height	130 cm
Weight (Vacuum Only)	117 kg.

Please note that specifications are subject to change without notice


Use only recommended tools & accessories



Activated Carbon Pellets - Included



Nitrile Suction Hose - Included



Strainer Basket for TE Series - Included



SS-25 AC TE (HY-C) raised