

European Headquarters

Tiger-Vac Europa S.R.L.
Via Marie Curie 17
Zona Industriale Ponte Rizzoli
Ozzano Emilia, BO 40064

Tel: ((39) 051 79.53.52)
Fax: ((39) 051 4695077)
Website: <http://www.tiger-vac.eu>
Email: info@tiger-vac.it

International Headquarters

Tiger-Vac International Inc.
2020 Dagenais Blvd. Ouest
Laval, Quebec
Canada H7L 5W2

Tel: (450-625-0099)
Fax: (450-625-3388)
Website: <http://www.tiger-vac.com>
Email: sales@tiger-vac.com



ATEX 3rd Party Certified



CE II 2GD

Ex h IIC T6 Gb
Ex h IIIC T85°C Db
LCIE 03 ATEX 6310 X



Ex h IIC T6 Gb
Ex h IIIC T85°C Db
IECEx LCIE 17.0076 X




GUARANTEED for the Safe Recovery
of Combustible/Conductive Dusts

ESD Safe Vacuum Systems for Hazardous
Locations are designed to prevent ignition
hazards.

We use metal parts or Static Dissipative
Powder Coating to prevent Electrostatic
Discharge (ESD)



EX Certified



Less than 10
ohms



Detachable
Tank



HEPA -
Included



High Filtration
Efficiency Unit



Dry Recovery



SS 304



Pharma
Applications

Specifications for SS-40/160L EX (RPS) RE HEPA TWIN VENTURI

Name	Part Number	Air Flow	Vacuum Pressure	Dry Recovery - Tank
SS-40 EX (RPS) RE HEPA TWIN VENTURI	110464	331 m ³ /h	5840 mm H ₂ O	151 L
	Dimensions: H196 cm x W86 cm x L81 cm Weight: 151 kg.			
Description: Specifications may vary depending upon performance of the compressor.				

Please note that specifications are subject to change without notice

Technical Sheet for SS-40/160L EX (RPS) RE HEPA TWIN VENTURI

HEPA FILTER AND ACCESSORIES - Included

Part #	Description
211027B	HEPA FILTER 99.995% EFFICIENCY ON 0.3 MICRON (CE VERSION)

REVERSE PULSE FILTER CARTRIDGE - Included

Part #	Description
214212A	FILTER CARTRIDGE, CONDUCTIVE ALUMINIZED SPUN BOND POLYESTER, 16" HIGH x 8.375" ID x 12.75" OD, 1" PLEATS

MUFFLER - Optional

Part #	Description
214735	MUFFLER ASSEMBLY FOR RE EXHAUST SYSTEM, STAINLESS STEEL WITH SOUND INSULATING FOAM

AIR SUPPLY HOSE ASSEMBLIES AND ACCESSORIES - Included

Part #	Description
214142	AIR SUPPLY HOSE ASSEMBLY SD* Ø0.75"(19mm)x50'(15m) WITH 1 MALE QUICK DISC & 1 FEMALE QUICK DISC

GROUND CONTINUITY TESTER - Included

Part #	Description
211065B	MULTIMETER

OIL AND WATER SEPARATORS - Optional	
Part #	Description
214196	OIL SEPARATOR 0.75"(19mm)
214200	WATER SEPARATOR 0.75"(19mm)

Ø2" (Ø50mm) STATIC CONDUCTIVE TOOLS AND ACCESSORIES (RESISTIVITY OF 10/3 - 10/5) - Optional	
Part #	Description
500540	CRUSHPROOF SUCTION HOSE ASMBLY 2"(50mm) x15'(4.5m) STATIC CONDUCTIVE w/2"(50mm) FEMALE CAMLOCK (ALUM
500538	CRUSHPROOF SUCTION HOSE (NO WIRE) Ø2"(50mm) STATIC CONDUCTIVE -BLACK (SOLD PER FOOT)
500160	WAND ONLY, SINGLE BEND, 2"(50mm) x 48" (122cm), ALUMINUM, WITH TAPER FOR FLOOR TOOL
500161A	UNIVERSAL TOOL Ø2"(50mm)x20"(51cm)SD* NO COUPLING WITH BRASS WHEELS&CONDUCTIVE BRISTLES&RUBBER BLADE
500156B	CREVICE TOOL SD* (NO COUPLING) Ø2"(50mm)x15"(38cm) -ALUMINUM
501184A	DUSTING BRUSH ALUMINUM SD* Ø2"(50mm)x5"(12.7cm)WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT
500230	CONICAL NOZZLE RUBBER SD* ASSEMBLY Ø2"(50mm)x7.5"(19cm) WITH Ø2"(50mm)PRESSURE FIT ALUM. CONNECTOR
500234	TIGER-CLAW RUBBER SD* ASSEMBLY Ø2"(50mm)x4.5"(11.5cm)WITH Ø2"(50mm)PRESSURE FIT ALUMINUM CONNECTOR
501200A	UTILITY TOOL SD* Ø2"(50mm)x8"(20.3cm) WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT -ALUMINUM

Ø2" (Ø50mm) EXPLOSION PROOF TOOLS & ACCESSORIES - MANDATORY FOR USE WHEN RECOVERING CONDUCTIVE, METAL & PYROTECHNIC DUST. STATIC DISSIPATIVE (LESS THAN 10 OHMS) - Optional	
Part #	Description
500306B	KANAFLEX SUCTION HOSE ASSEMBLY SD* Ø2"(50mm)x15'(4.5m)WITH Ø2" FEMALE CAMLOCK,HOSE CUFF&RING
500300	KANAFLEX SUCTION HOSE ONLY SD* Ø2"(50mm) CONDUCTIVE&ABRASION RESISTANT (SOLD PER FOOT)
500160SS	WAND ONLY SINGLE BEND Ø2"(50mm)x48"(1.2m) -STAINLESS STEEL AISI 304 FOR HOSE CUFF & RING
500161A	UNIVERSAL TOOL Ø2"(50mm)x20"(51cm)SD* NO COUPLING WITH BRASS WHEELS&CONDUCTIVE BRISTLES&RUBBER BLADE
500156B	CREVICE TOOL SD* (NO COUPLING) Ø2"(50mm)x15"(38cm) -ALUMINUM
501184A	DUSTING BRUSH ALUMINUM SD* Ø2"(50mm)x5"(12.7cm)WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT
500230	CONICAL NOZZLE RUBBER SD* ASSEMBLY Ø2"(50mm)x7.5"(19cm) WITH Ø2"(50mm)PRESSURE FIT ALUM. CONNECTOR
500234	TIGER-CLAW RUBBER SD* ASSEMBLY Ø2"(50mm)x4.5"(11.5cm)WITH Ø2"(50mm)PRESSURE FIT ALUMINUM CONNECTOR
501200A	UTILITY TOOL SD* Ø2"(50mm)x8"(20.3cm) WITH CONDUCTIVE BRISTLES & TUBE FOR PRESSURE FIT -ALUMINUM